

The JLD FRESH AIR HOSE APPARATUS consists of an ISI marked PROTECT 2000 Full Face Mask connected to a corrugated tube ending in a manifold mounted on a harness belt worn around the waist. The manifold is connected to a 15 meters long 20mm I.D. canvas covered wire-embedded rubber hose. The other end of the hose is connected to the electrical / hand operated blower.

The electrical / hand operated radial blower is a portable unit mounted on a steel frame and housed in a sturdy steel carrying box. It is capable of providing fresh air to 2 persons simultaneously at a minimum flow of 50 LPM. The single phase Flame proof motor conforms to groups 2A

and 2B. In case of power failure, the blower can be used instantaneously in the manual mode, thus causing no discomfort to the wearer.

A Nylon or Manila signaling rope can be spliced on to the belt for signaling between the wearer and operator of the blower. Also available is a wire-embedded hemp-covered life line which can be used in the event of the wearer falling into a confined space and having to be hauled out.

Option: Also available two hose lengths of 15m / 18m joined by a coupling to be used only in horizontal position work situation.

Ordering information

1 Fresh Air Hose
Apparatus with
Manually /
Electrically
Operated
Blower for
single user

Fresh Air Hose Apparatus with Manually /Electrically Operated Blower for single user Comprising of following:

- 1. Portable Unit, mounted on wheels
- **2.** Blower: Both manually as well as electrically operated to ensure fresh air supply of 50 to 60 litres/min at each face mask
- **3.** Motor: Flame proof, conforming to Class-I, Div. II: Gas Group II, iiB;

Operating Voltage: 220/230 V, Single Phase

- 4. Tapping Points: 2 nos.
- **5.** i) Hose: 20MM ID x 30m canvas covered wire embedded rubber hose with coupling (2 nos.15m hoses connected with coupling)
- ii) Life Line: One length of 32m Nylon lifeline for transmitting signals
- iii) Protect 2000 Face Mask: 1 No. (ISI Marked) with double sealing frame, speech diaphragm, self-demisting inner mask with corrugated tube connected to manifold mounted on a harness belt at the waist

D-4017

2 Fresh Air Hose
Apparatus with
Manually /
Electrically
Operated
Blower for
two user

Fresh Air Hose Apparatus with Manually /Electrically Operated Blower for two user. It Comprises of:

D-4018

- 1. Portable Unit, mounted on wheels
- 2. Blower: Both manually as well as electrically operated to ensure fresh air supply of 50 to 60 liters/min at each face mask
- 3. Motor: Flame proof, conforming to Class-I, Div. II: Gas Group II, iiB;

Operating Voltage: 220/230 V, Single Phase

- 4. Tapping Points: 2 Nos.
- **5.** i) Hose: 20MM ID x 15m x 2 canvas covered wire embedded rubber hoses with necessary connection
- ii) Life Line: Two length of 17m Nylon lifeline for transmitting signals
- iii) Protect 2000 Face Mask: 2 Nos. (ISI Marked) with double sealing frame, speech diaphragm, self-demisting inner mask with corrugated tube connected to manifold mounted on a harness belt at the waist

Joseph Leslie **Dynamiks**

formerly known as Joseph Leslie Draeger

Joseph Leslie Dynamiks Mfg. Pvt. Ltd. **Head Office Mumbai**: Leslico House, Prof. V.S.Agashe Road, Dadar West, Mumbai 400028. India. **T** +91 22 24227198/1880/1878, +91 22 24376651, **F** +91 22 24303705, **E** mumbai@jldmail.com • **Vasai**: Vora Industrial Estate, Bhoidapada, Sativali Road, Vasai East, Thane 401208. India. **T** +91 250 6456501 - 24, **F** +91 22 24303705 • **Chennai**: #6/3 Avenue Road, Nungambakkam, Chennai 600034. India. **T** +91 44 42028455/42146053, **F** +91 44 28250289, **E** chennai@jldmail.com • **New Delhi**: Office #701, 95, Vishal Bhawan, Nehru Place, New Delhi 110019. India. **T** +91 11 41808300/1/2/3, **F** +91 11 26211685, **E** delhi@jldmail.com • **Kolkata**: 12-F, Everest House, 46-C Jawaharlal Nehru Road, Kolkata 700071. India. **T** +91 33 22883107/22882467/30523108, **F** +91 33 22889644, **E** kolkata@jldmail.com **www.josephlesliedynamiks.com An ISO 9001:2008 Company**